ELECTROMAGNETIC FLOW TRANSMITTER (INSERTION TYPE)

Special Features:

Intelligent Flow Meter with Optional HART

High Accuracy with High Repeatability

Wide Measurement Range, upto 10:1

No Moving Parts, Reducing the Maintenance

Inbuilt LCD Display with Setting Keypad

Optionally available for High Pressure Applications

Applications:

F6700 Electromagnetic Flow Meter with new engineering innovations, has all the desired features to ever changing needs of industries like Paper, Cement,

Textile, Power, Pharmaceutical, Process, Dairy and Water Management.

A perfect answer to almost any application, regardless of size

(From 150 MM to 3000MM), F6700 withstands the rigors of industrial demands.

Performance Specifications:

Media : Liquids

Line Size : 150MM to 3000MM

Accuracy : $\pm 0.5\%$ For Liquids Repeatability : $\pm 0.2\%$ For Liquids

Output : 4 - 20mA, 2 Wire (Optional with HART)

Power Supply : 12VDC / 24VDC / Li-on 3.6V 14Ah / 220V AC

Alarms : Optional

Password Protection: Yes

Media Temperature : - 40 °C to 250 °C / Optional -40 °C to 350 °C

Ambient Temp. : $-40 \,^{\circ}\text{C}$ to $85 \,^{\circ}\text{C}$

Maximum Pressure: 25 Bar

Sensor MOC : AISI 316LSS (Other Materials Optional)

Protection Grade : IP65

Display : In Built LCD Display

Advantages of F6700:

Proven High Reliability with More than 15 years of Experience

Low Cost of Installation

Pre Calibrated at Factory, No Field Calibration Required

Very Low Pressure loss results in considerable enery savings

Zero Maintenance as there are no moving or rotating parts

True Volumetric Output is available from the Flow Indicator

ELECTROMAGNETIC FLOW TRANSMITTER (INSERTION TYPE)

HOW TO ORDER

Output:	F6700I
01 4 - 20mA02 4 - 20mA with superimposed HART	01
	Φ
Power Supply:	02
01 12V DC	
02 24V DC	
03 Li-ion 3.6V 14Ah	
Media Temperature:	01
01 -40 ~ 250°C	
02 -40 ~ 350°C	
	Φ
Accuracy:	01
01 ±1.0% of F.S	
02 ±0.5% of F.S	
	ф
🌣 Flange Type:	01
01 Clamp Type	
02 Integral Type	
* * · · · · · · · · · · · · · · · · · ·	·
Aperture Size (Line Size):	100
150 6 Inch	
200 8 Inch	
250 10 Inch	
300 12 Inch	
350 14 Inch	
400 16 Inch	
500 20 Inch	
600 24 Inch	
	¤
Ordering Example: F6700-01-02-01-01-100	